## **Knightsbridge**

## DATASHEET




## G4LED6





www.mlaccessories.co.uk



MLA PART CODE	G4LED6
DESCRIPTION	G4 LED 1.5W AC/DC 4000K
NET WEIGHT (KG)	0.003
DIFFUSER	Frosted
DIMENSIONS (MM)	Diameter - 10.2 Height - 32
CONSTRUCTION	Construction - Thermoplastic
CLASS	III
IP RATING	IP20
WATTAGE (W)	1.5
LAMP TECHNOLOGY	LED
LAMP BASE	G4
LUMENS (LM)	110
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	101.62
CIRCUIT WATTAGE (W)	1.1
ССТ	4000K
LIGHT COLOUR	Cool White
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.093
DISPLACEMENT FACTOR	>0.7
SVM	0.025
PST-LM	0.021
BEAM ANGLE (DEGREES)	120
LIFE SPAN (HRS)	25,000
L70B50 LIFESPAN (HRS)	25,000
LED COMPATIBLE	Yes
DIMMABLE	No





## Knightsbridge

OPERATING TEMPERATURE	40°C
INPUT VOLTAGE	12V AC/DC
WARRANTY	3year(s)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5055832934349

Date Created: 11/06/2024 13:47







ML Accessories Ltd. reserves the right to withdraw, improve, or modify any design without prior notification. ML Accessories Ltd. cannot be held responsible for the incorrect application of any product.