


## DATASHEET



### BATS5H

230V 5ft 55W LED High Lumen Batten- 4000K

[www.mlaccessories.co.uk](http://www.mlaccessories.co.uk)



| MLA PART CODE                 | BATS5H   |
|-------------------------------|--|
| DESCRIPTION                   | 230V 5ft 55W LED High Lumen Batten- 4000K                        |
| NET WEIGHT (KG)               | 1.5  |
| FINISH                        | White  |
| DIFFUSER                      | Opal   |
| DIMENSIONS (MM)               | Length - 1525<br>Width - 61<br>Projection - 71                   |
| CONSTRUCTION                  | Construction - Pressed steel<br>Construction 2 - & polycarbonate |
| CLASS                         | I  |
| IP RATING                     | IP20   |
| WATTAGE (W)                   | 55   |
| LAMP TECHNOLOGY               | LED  |
| LAMP INCLUDED                 | Yes  |
| LUMENS (LM)                   | 5925   |
| LUMENS LIGHT SOURCE ONLY (LM) | 8210   |
| LUMEN TOLERANCE               | 5%   |
| EFFICACY (LM/W)               | 147.49   |
| CIRCUIT WATTAGE (W)           | 55.68  |
| CCT                           | 4000K  |
| LIGHT COLOUR                  | Cool White   |
| CRI                           | >80  |
| SDCM                          | <6   |
| RUNNING CURRENT (A)           | 0.252  |
| DISPLACEMENT FACTOR           | >0.9   |
| SVM                           | 0.873  |
| PST-LM                        | 0.035  |
| BEAM ANGLE (DEGREES)          | 135  |
| LIFE SPAN (HRS)               | 50,000   |

|  |   |
|--|---|
| L70B50 LIFESPAN (HRS)                    | 50,000  |
| DIMMABLE                                 | No  |
| OPERATING TEMPERATURE                    | -20~50°C  |
| INPUT VOLTAGE                            | 230V 50Hz   |
| CABLE GLAND INCLUDED                     | No  |
| DRIVER                                   | DRIVER TYPE - Constant Current<br>MAX. OUTPUT - 50W<br>OUTPUT VOLTAGE - 29-43V<br>OUTPUT CURRENT - 1200mA<br>POWER FACTOR - 0.95<br>EFFICIENCY FULL LOAD - 91.33<br>ISOLATION - SELV<br>AMBIENT TEMPERATURE (Ta) - -20~50°C<br>CASE TEMPERATURE (Tc) - 75°C |
| WARRANTY                                 | 5year(s)  |
| MANUFACTURED IN ACCORDANCE WITH          | BS EN 60598   |
| ORIGIN OF MANUFACTURE                    | China   |
| DECLARATION OF CONFORMITY (HELD ON FILE) | Yes   |
| EAN                                      | 5056270803440   |

Date Created: 11/06/2024 17:32

