

## DATASHEET



### EMPOWER4

**230V IP20 3.5W LED Emergency Downlight 5500K  
(maintained/non-maintained use)**

[www.mlaccessories.co.uk](http://www.mlaccessories.co.uk)

MLA PART CODE	EMPOWER4
DESCRIPTION	230V IP20 3.5W LED Emergency Downlight 5500K (maintained/non-maintained use)
NET WEIGHT (KG)	0.22
FINISH	White
DIMENSIONS (MM)	Diameter - 60 Length - 183 Recessed Depth - 32 Minimum Void - 80
CUT-OUT (MM)	Cut-out Diameter - 45
CONSTRUCTION	Construction - Polycarbonate
CLASS	II
IP RATING	IP20
WATTAGE (W)	3.5
LAMP TECHNOLOGY	LED
LAMP INCLUDED	Yes
LUMENS (LM)	140
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	40
LUMENS EMERGENCY MODE (LM)	140
CIRCUIT WATTAGE (W)	3.5
CCT	5500K
LIGHT COLOUR	Daylight
CRI	>70
RUNNING CURRENT (A)	0.027
BEAM ANGLE (DEGREES)	140
L70B50 LIFESPAN (HRS)	30000
DIMMABLE	No
EMERGENCY	Maintained / Non-maintained / Switched
SELF-TEST	No

IC RATED	No
OPERATING TEMPERATURE	0~25°C
INPUT VOLTAGE	230V 50Hz
CABLE LENGTH (M)	0.35
CABLE TYPE	H05VV-F
BATTERY INCLUDED	Yes
WARRANTY	5year(s)
WARRANTY INFORMATION	including battery
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270877595

Date Created: 11/06/2024 20:22

