Xnightsbridge

DATASHEET




FLTPW

230V IP65 18W LED White Twin Spot Floodlight with

PIR

www.mlaccessories.co.uk



MLA PART CODE	FLTPW
DESCRIPTION	230V IP65 18W LED White Twin Spot Floodlight with PIR
NET WEIGHT (KG)	1.03
FINISH	White
DIFFUSER	Clear
DIMENSIONS (MM)	Height - 120 Width - 205 Projection - 150 Base Width - 165 Base Depth - 25
CONSTRUCTION	Construction - Die-cast aluminium
CLASS	I
IP RATING	IP65
WATTAGE (W)	18
LAMP TECHNOLOGY	CoB LED
LAMP INCLUDED	Yes
LUMENS (LM)	1455
LUMENS LIGHT SOURCE ONLY (LM)	1870
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	100.57
CIRCUIT WATTAGE (W)	18.6
ССТ	3500K
LIGHT COLOUR	White
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.093
DISPLACEMENT FACTOR	>0.9
SVM	3.041
PST-LM	0.07
BEAM ANGLE (DEGREES)	45





Xnightsbridge

LIFE SPAN (HRS)	25,000
L70B50 LIFESPAN (HRS)	50,000
DIMMABLE	No
OPERATING TEMPERATURE	35°C
INPUT VOLTAGE	230V 50Hz
CABLE ENTRY (MM)	20
CABLE GLAND INCLUDED	Blind grommet
SENSOR TYPE	PIR
SENSOR OVERRIDE	Yes
SENSOR DETECTION ANGLE (DEGREES)	120
OPTIMUM DETECTION RANGE (M)	Maximum 8
SENSOR DURATION	90 seconds (non-adjustable)
SENSOR LUX SETTINGS	30 lux (non-adjustable)
WARRANTY	3year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5055832950745

Date Created: 11/06/2024 13:59





