



DATASHEET



T8BLED15

230V 26W LED Batten 1525mm (5ft) 4000K

www.mlaccessories.co.uk



MLA PART CODE	T8BLED15
DESCRIPTION	230V 26W LED Batten 1525mm (5ft) 4000K
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 1525 Width - 60 Projection - 85
CONSTRUCTION	Construction - Pressed steel Construction 2 - & polycarbonate
CLASS	I
IP RATING	IP20
WATTAGE (W)	26
LAMP TECHNOLOGY	LED
LAMP INCLUDED	Yes
LUMENS (LM)	3000
LUMENS LIGHT SOURCE ONLY (LM)	3325
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	113
CIRCUIT WATTAGE (W)	24.65
CCT	4000K
LIGHT COLOUR	Cool White
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.114
DISPLACEMENT FACTOR	>0.9
SVM	0.825
PST-LM	0.038
BEAM ANGLE (DEGREES)	120
LIFE SPAN (HRS)	30,000
L70B50 LIFESPAN (HRS)	50,000

DIMMABLE	No
OPERATING TEMPERATURE	-15~45°C
INPUT VOLTAGE	230V 50Hz
CABLE ENTRY (MM)	20
CABLE GLAND INCLUDED	No
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 30W OUTPUT VOLTAGE - 34-49V OUTPUT CURRENT - 600mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 87.89 ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - -15~45°C CASE TEMPERATURE (Tc) - 70°C
WARRANTY	5year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5055832934554

Date Created: 11/06/2024 13:47

