


## DATASHEET



### BT9ACTB

230V IP65 9W CCT Adjustable LED Bulkhead C/W Black Trim

[www.mlaccessories.co.uk](http://www.mlaccessories.co.uk)



| MLA PART CODE                 | BT9ACTB   |
|-------------------------------|---|
| DESCRIPTION                   | 230V IP65 9W CCT Adjustable LED Bulkhead C/W Black Trim |
| NET WEIGHT (KG)               | 0.6   |
| FINISH                        | Black   |
| DIFFUSER                      | Opal  |
| DIMENSIONS (MM)               | Diameter - 256<br>Projection - 74                       |
| CONSTRUCTION                  | Construction - Polycarbonate                            |
| CLASS                         | II  |
| IP RATING                     | IP65  |
| IK RATING                     | IK08  |
| WATTAGE (W)                   | 9   |
| LAMP TECHNOLOGY               | SMD LED   |
| LAMP INCLUDED                 | Yes   |
| LUMENS (LM)                   | 730 / 810 / 780   |
| LUMENS LIGHT SOURCE ONLY (LM) | 900   |
| LUMEN TOLERANCE               | 5%  |
| EFFICACY (LM/W)               | 118.41  |
| CIRCUIT WATTAGE (W)           | 7.617   |
| CCT                           | 3000/4000/5700K   |
| LIGHT COLOUR                  | CCT   |
| CRI                           | >80   |
| SDCM                          | <6  |
| RUNNING CURRENT (A)           | 0.036   |
| DISPLACEMENT FACTOR           | >0.9  |
| SVM                           | 0.536   |
| PST-LM                        | 0.025   |
| BEAM ANGLE (DEGREES)          | 115   |
| LIFE SPAN (HRS)               | 30,000  |

|  |  |
|--|--|
| L70B50 LIFESPAN (HRS)                    | 50,000   |
| LED COMPATIBLE                           | Yes  |
| DIMMABLE                                 | No   |
| OPERATING TEMPERATURE                    | -20~50°C   |
| INPUT VOLTAGE                            | 230V 50Hz  |
| CABLE ENTRY (MM)                         | 20   |
| CABLE GLAND INCLUDED                     | Blind grommet  |
| DRIVER                                   | DRIVER TYPE - Constant Current<br>MAX. OUTPUT - 8.6W<br>OUTPUT VOLTAGE - 30 - 43V<br>OUTPUT CURRENT - 200mA<br>POWER FACTOR - 0.95<br>EFFICIENCY FULL LOAD - 80<br>ISOLATION - SELV<br>AMBIENT TEMPERATURE (Ta) - -20~50°C<br>CASE TEMPERATURE (Tc) - 75°C |
| WARRANTY                                 | 5year(s)   |
| MANUFACTURED IN ACCORDANCE WITH          | BS EN 60598  |
| ORIGIN OF MANUFACTURE                    | China  |
| DECLARATION OF CONFORMITY (HELD ON FILE) | Yes  |
| EAN                                      | 5056270827972  |

Date Created: 11/06/2024 18:56

