Xnightsbridge


DATASHEET



BATSCDA4

230V 4ft 32W DALI CCT Adjustable Batten

www.mlaccessories.co.uk



MLA PART CODE	BATSCDA4
DESCRIPTION	230V 4ft 32W DALI CCT Adjustable Batten
NET WEIGHT (KG)	1.35
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 1225 Width - 61 Projection - 71
CONSTRUCTION	Construction - Pressed steel Construction 2 - & polycarbonate
CLASS	I
IP RATING	IP20
WATTAGE (W)	32
LAMP TECHNOLOGY	LED
LUMENS (LM)	3790/4480/4120
LUMENS LIGHT SOURCE ONLY (LM)	4970
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	157.16
CIRCUIT WATTAGE (W)	31.66
ССТ	3000/4000/5700K
LIGHT COLOUR	CCT
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.141
DISPLACEMENT FACTOR	>0.9
SVM	0
PST-LM	0
BEAM ANGLE (DEGREES)	105
L70B50 LIFESPAN (HRS)	60,000
OPERATING TEMPERATURE	-20~40°C





Xnightsbridge

INPUT VOLTAGE	230V 50Hz
CABLE GLAND INCLUDED	No
DRIVER	DRIVER TYPE - DALI MAX. OUTPUT - 31.5W OUTPUT VOLTAGE - 25-42V OUTPUT CURRENT - up to 750mA POWER FACTOR - 0.9 EFFICIENCY FULL LOAD - 95 ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - 50°C CASE TEMPERATURE (Tc) - 90°C
STANDBY POWER	≤ 0.5WW
WARRANTY	5year(s)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270881707

Date Created: 11/06/2024 20:28





