



DATASHEET



BATSCDA5

230V 5ft 40W DALI CCT Adjustable Batten

www.mlaccessories.co.uk



MLA PART CODE	BATSCDA5
DESCRIPTION	230V 5ft 40W DALI CCT Adjustable Batten
NET WEIGHT (KG)	1.63
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 1525 Width - 61 Projection - 71
CONSTRUCTION	Construction - Pressed steel Construction 2 - & polycarbonate
CLASS	I
IP RATING	IP20
WATTAGE (W)	40
LAMP TECHNOLOGY	LED
LUMENS (LM)	4960/5720/5410
LUMENS LIGHT SOURCE ONLY (LM)	6330
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	157.82
CIRCUIT WATTAGE (W)	40.15
CCT	3000/4000/5700K
LIGHT COLOUR	CCT
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.179
DISPLACEMENT FACTOR	>0.9
SVM	0
PST-LM	0
BEAM ANGLE (DEGREES)	145
L70B50 LIFESPAN (HRS)	60,000
OPERATING TEMPERATURE	-20~40°C

INPUT VOLTAGE	230V 50Hz
CABLE GLAND INCLUDED	No
DRIVER	DRIVER TYPE - DALI MAX. OUTPUT - 44.1W OUTPUT VOLTAGE - 25-42V OUTPUT CURRENT - up to 1050mA POWER FACTOR - 0.9 EFFICIENCY FULL LOAD - 93 ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - 50°C CASE TEMPERATURE (Tc) - 90°C
STANDBY POWER	≤ 0.5WW
WARRANTY	5year(s)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270881714

Date Created: 11/06/2024 20:28

