Xnightsbridge


DATASHEET



BATSCWST6

230V 6ft 27/52W CCT Adjustable Self-Test Emergency Batten

www.mlaccessories.co.uk



| MLA PART CODE | BATSCWST6 |
|-------------------------------|---|
| DESCRIPTION | 230V 6ft 27/52W CCT Adjustable Self-Test Emergency Batten |
| NET WEIGHT (KG) | 2.09 |
| FINISH | White |
| DIFFUSER | Opal |
| DIMENSIONS (MM) | Length - 1790 Width - 61 Projection - 71 |
| CONSTRUCTION | Construction - Pressed steel Construction 2 - & polycarbonate |
| CLASS | I |
| IP RATING | IP20 |
| WATTAGE (W) | 27/52 |
| LAMP TECHNOLOGY | LED |
| LUMENS (LM) | 3750/4170/4070, 6590/7520/7150 |
| LUMENS LIGHT SOURCE ONLY (LM) | 8410 |
| LUMEN TOLERANCE | 5% |
| EFFICACY (LM/W) | 165.5 |
| LUMENS EMERGENCY MODE (LM) | 310 |
| CIRCUIT WATTAGE (W) | 50.82 |
| ССТ | 3000/4000/5700K |
| LIGHT COLOUR | ССТ |
| CRI | >85 |
| SDCM | <6 |
| RUNNING CURRENT (A) | 0.223 |
| DISPLACEMENT FACTOR | >0.9 |
| SVM | 0 |
| PST-LM | 0 |
| BEAM ANGLE (DEGREES) | 145 |
| L70B50 LIFESPAN (HRS) | 60,000 |





Xnightsbridge

| DIMMABLE | No |
|--|---|
| EMERGENCY | Maintained / Non-maintained / Switched |
| SELF-TEST | Yes |
| OPERATING TEMPERATURE | -5~50°C |
| INPUT VOLTAGE | 230V 50Hz |
| CABLE GLAND INCLUDED | No |
| DRIVER | DRIVER TYPE - Constant Current MAX. OUTPUT - 26/52W OUTPUT VOLTAGE - 30-43V OUTPUT CURRENT - 600/1200mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 96.8 ISOLATION - SELV AMBIENT TEMPERATURE (Ta)20~50°C CASE TEMPERATURE (Tc) - 75°C |
| BATTERY INCLUDED | Yes |
| WARRANTY | 5year(s) |
| WARRANTY INFORMATION | (excluding battery) |
| ORIGIN OF MANUFACTURE | China |
| DECLARATION OF CONFORMITY (HELD ON FILE) | Yes |
| EAN | 5056270881516 |

Date Created: 11/06/2024 20:28





